



every solution is **unique.**

**R100 Platform**

**Refrigerated Water Recirculating Systems**

R100 platform

	with air cooled condenser	with water cooled condenser
Cooling Capacity <small>(at 65°F/18°C supply water temp.)</small>	Watts 3,150 Btu/Hr 10,740	Watts 3,850 Btu/Hr 13,125
Compressor HP	1	1
Refrigerant <small>alternatives available</small>	R134a	R134a
Water Pump Capacity <small>alternatives available</small>	1.7 GPM (6.4 LPM)	1.7 GPM (6.4 LPM)
Pump Motor HP	1/3	1/3
Reservoir Volume	6 Gallons (23 Liters)	6 Gallons (23 Liters)
Power Requirements <sup>1</sup> <small>alternatives available</small>	208/230V-1Ø-60Hz	208/230V-1Ø-60Hz
Dimensions (W x D x H)	53 x 74 x 81 cm 21 x 29 x 32 in.	53 x 74 x 81 cm 21 x 29 x 32 in.
Shipping Weight	350 Lbs. (159 Kg)	350 Lbs. (159 Kg)

- **Unit specifications will change by adding certain options.**
  - Cooling capacity of air-cooled units is based on 80°F/27°C ambient air temperature. Allowable ambient temperature range is 55°F to 90°F (13°C to 32°C). Changes in air temperature will affect cooling capacity. See Haskris Options (I) and/or (J) to operate outside this range.
- <sup>1</sup> Also available in 50Hz—contact Haskris



**Haskris Company**

100 Kelly Street  
Elk Grove Village, Illinois  
60007 USA

Phone: 001-847-956-6420

Fax: 001-847-956-6595

Email: sales@haskris.com